



(12)

EUROPEAN PATENT APPLICATION

(43) Dat of publication:
29.08.2001 Bulletin 2001/35

(51) Int Cl.7: **B60L 11/12**

(21) Application number: 01103474.1

(22) Date of filing: 14.02.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:

- **Takashi, Yanase,**
c/o Mitsubishi Jidosha Kogyo K.K.
Tokyo (JP)
- **Makoto, Ogata,**
c/o Mitsubishi Jidosha Kogyo K.K.
Tokyo (JP)

(30) Priority: 16.02.2000 JP 2000038602

**(71) Applicant: Mitsubishi Jidosha Kogyo Kabushiki Kaisha
Tokyo 108-8410 (JP)**


(74) Representative: **Kern, Ralf M., Dipl.-Ing.**
Hansastraße 16/II.
80686 München (DE)

(54) Warm-up control device of hybrid electric vehicle

(57) The invention provides a warm-up control device of a hybrid electric vehicle, which warms up an engine for generator while extending the life of the engine and improves the quietness. If an engine temperature is not greater than a set temperature after the start of

the engine for generator, the warm-up control device controls a load of the generator and controls an engine output in accordance with the load of the generator so as to maintain an engine revolution speed at a predetermined low revolution speed.

Fig. 1



Description**BACKGROUND OF THE INVENTION****Field of the Invention**

[0001] The present invention generally relates to a hybrid electric vehicle, and more particularly to a technique for warming up an engine for generator.

Description of Related Art

[0002] In recent years, there has been developed a series hybrid vehicle, that is a vehicle equipped with a motor as a source of driving force for the vehicle and a secondary battery, which supplies power to the motor, that is charged by a generator driven by a relatively-small engine. Normally, the series hybrid vehicle operates the engine to run the generator in order to charge the battery if a charging level (SOC: state of charge) of the battery is low.

[0003] In general, the series hybrid vehicle, however, does not always charge the battery while the vehicle is running, but charges the battery if the engine is cold after being static for a long period of time. Therefore, if the engine is cold and a large amount of power is required to be generated, the forcible increase in an engine output increases fuel consumption causing a deterioration in fuel economy and also increases oil consumption. This shortens the life of the engine.

[0004] To address this problem, Japanese Patent Provisional Publication No. 5-328528 discloses a device, which raises an engine revolution speed to warm up an engine used to drive a generator when the engine is cold.

[0005] The rise in the engine revolution speed as disclosed in the above publication, however, results in the increase in noise and vibration. Moreover, if the engine is cold and is not completely smooth, the rise in the engine revolution speed results in the damage on each sliding part of the engine. The increase in the noise and vibration and the damage on each sliding part shorten the life of the engine.

SUMMARY OF THE INVENTION

[0006] It is therefore an object of the present invention to provide a warm-up control device of a hybrid electric vehicle, which warms up an engine used to drive a generator while extending the life of the engine and improves the quietness.

[0007] The above object can be accomplished by providing a hybrid electric vehicle comprising: a generator being rotated by a driving force of an engine to generate power and supply the power to a battery or a motor; a temperature sensing device for sensing a temperature of the engine; and a warm-up control device for controlling a load of the generator and an output of the engine

so as to maintain a revolution speed of the engine at a predetermined revolution speed, if the temperature of the engine sensed by the temperature sensing device is not greater than a set temperature.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The nature of this invention, as well as other objects and advantages thereof, will be explained in the following with reference to the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures and wherein:

Fig. 1 is a schematic diagram showing a series hybrid vehicle, to which a warm-up control device of a hybrid electric vehicle according to the present invention is applied;

Fig. 2 is a flow chart showing a control routine of a warm-up control according to the present invention; and

Fig. 3 is a drawing showing a relationship between a generator revolution speed $N_g (=N_e)$ and a generated torque T_g , i.e., load, and a drawing showing a relationship between a load equivalent to a small power generation (the first set load T_{g1} : black circle) and a load equivalent to a medium power generation (the second set load T_{g2} : white circle).

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0009] A preferred embodiment of the present invention will be described hereinbelow.

[0010] Fig. 1 is a schematic diagram showing a series hybrid vehicle, to which a warm up control device of a hybrid electric vehicle according to the present invention is applied. With reference to Fig. 1, there will now be described the structure of the warm up control device of the hybrid electric vehicle according to the present invention. For example, a large vehicle such as an omnibus, which runs at a low speed in a city, is supposed to be the series hybrid vehicle.

[0011] As shown in Fig. 1, the series hybrid vehicle is equipped with a traction motor 10 as a source of driving force. The traction motor 10 is electrically connected to a high-voltage secondary battery 12, which supplies power, through an inverter 14. The traction motor 10 is, e.g., an induction motor, but may also be a permanent electromagnet synchronous type motor.

[0012] When the vehicle is braked, the traction motor 10 functions as an energy regenerative brake, i.e., a generator that utilizes braking energy. More specifically, when a driver of the vehicle operates a brake (not shown), the traction motor 10 generates a braking force and power at the same time. The generated power is charged in the battery 12. The inverter 14 supplies stable power to the traction motor 10 by adjusting a voltage and a current supplied from the battery 12 or a later-

described generator 22, or supplies stable power to the battery 12 by adjusting a voltage and a current generated by the traction motor 10.

[0013] As shown in Fig. 1, a pair of driving wheels WR, WL is connected to a rotary shaft of the traction motor 10 through reduction gears 16 and a differential gear 18. The reduction gears 16 are not necessarily always provided. The battery 12 and the inverter 14 are electrically connected to the generator 22 through the other inverter 20. A rotary shaft of the generator 22 is connected to an output shaft of an engine 24, which is an internal combustion engine for generator. The generator 22 is, i.e., a permanent electromagnet type generator.

[0014] The inverter 20 is also electrically connected to an auxiliary motor 26, which drives auxiliaries such as an air compressor 27 for an air brake and a power steering pump 28. As is the case with the inverter 14, the inverter 20 supplies stable power to the battery 12 or the traction motor 10 by adjusting a voltage and a current generated by the generator 22, or supplies stable power to the auxiliary motor 26 by adjusting the voltage and the current from the battery 12. The inverter 20 also has a function of adjusting the voltage and the current from the battery 12 and supplying them to the generator 22.

[0015] A relay fuse 30 is mounted between the battery 12 and the inverters 14, 20. The relay fuse 30 is electrically connected to the inverter 14, and allows a current to flow from the battery 12 to the traction motor 10 or prevents an excessive current from flowing from the battery 12 to the traction motor 10 in accordance with information from the inverter 14. The relay fuse 30 also has a function of preventing the generator 22 or traction motor 10 during the regenerative braking (the engine regeneration) from excessively charging the battery 12.

[0016] As shown in Fig. 1, the battery 12 and the inverters 14, 20 are electrically connected to an electronic control unit (ECU) 40 so that the battery 12 and the inverter 14, 20 can communicate with the ECU 40. The inverter 14 and the inverter 20 are electrically connected to the traction motor 10 and the generator 22, respectively, so that they can communicate with one another. The ECU 40 is connected to a battery controller 46, which monitors a charging level (SOC: state of charging), etc. of the battery 12, and an engine controller 48, which controls the operation of the engine 24. The engine controller 48 also has a function of sensing an engine revolution speed Ne and sensing an engine temperature Te from a coolant temperature of the engine 24 (a temperature sensing device).

[0017] In the hybrid vehicle that is constructed in the above-mentioned manner, a required motor torque signal corresponding to a control input of an accelerator pedal (not shown) is supplied to the inverter 14 while the vehicle is running. In accordance with the signal, the inverter 14 adjusts the voltage and the current from the battery 12, and therefore, the traction motor 10 generates a desired motor torque. If the battery controller 46

senses a drop in SOC of the battery 12, the engine controller 48 starts the engine 24 to operate the generator 22, which generates power to charge the battery 12 in accordance with SOC. If SOC of the battery 12 is low, the power equivalent to a power consumption of the traction motor 10 is directly fed from the generator 22 to the traction motor 10 so that the surplus power from the generator 22 can be charged in the battery 12.

[0018] If, for example, a brake pedal (not shown) is operated to brake the vehicle and the control input of the accelerator pedal is zero, the traction motor 10 performs the regenerative braking and generates power to charge the battery 12. While the vehicle is running, the power from the battery 12 appropriately runs the auxiliary motor 26 in order to drive the auxiliaries such as the compressor 27 and the power steering pump 28.

[0019] If SOC of the battery 12 is decreased, the engine 24 is started to cause the generator 22 to generate the power as stated above. If, however, the engine 24 is static for a long period of time, the engine 24 becomes cold. Thus, the engine 24 must be warmed up in order to acquire a stable output. There will now be described the operation of the warm-up control device in the hybrid electric vehicle, i.e., the warm-up control for the engine 24.

[0020] Fig. 2 is a flow chart showing a control routine of the warm-up control according to the present invention, which is executed by the ECU 40. A description will hereunder be given with reference to the flow chart. When a drop in SOC of the battery 12 is sensed in accordance with the information from the battery controller 46, the engine controller 48 starts the engine 24. First, it is determined in a step S10 whether the engine 24 has been started or not in accordance with the information from the engine controller 48. If yes, the process goes to a step S12.

[0021] In the step S12, it is determined whether the engine temperature Te is higher than a preset temperature (Tw) ($Te > Tw$) or not in accordance with the engine temperature information Te from the engine controller 48. If yes, the process goes out of the routine. If no, the process goes to a step S14.

[0022] In the step S14, it is determined whether the engine temperature Te is higher than a first preset first temperature Twa ($Twa < Tw$) ($Te < Twa$) or not. If yes, i.e., the engine temperature Te is determined as being higher than the first preset temperature Twa and being not greater than the set temperature Tw, the process goes to a step S16.

[0023] In the step S16, a small power generation load is applied. More specifically, a load equivalent to a small power generation (the first set load) is applied to the engine 24 to thereby warm up the engine 24. In more detail, the small power generation load (the first set load) is applied to the generator 22 in order to cause the generator 22 to generate a small amount of power. On the other hand, the engine controller 48 issues an engine output command to the engine 24 in order to maintain

the engine revolution speed N_e at a predetermined low revolution speed N_{el} (e.g., 500rpm) against the small power generation load (the first set load) of the generator 22. More specifically, a fuel injection information is supplied to a fuel injection valve (not shown) of the engine 24 in order to make it possible to maintain the engine revolution speed N_e at the predetermined low revolution speed N_{el} against the small power generation load (the first set load) of the generator 22.

[0024] Therefore, the engine 24 injects a larger quantity of fuel from the fuel injection valve than fuel required for operating the unloaded generator 22 to thereby achieve an engine output in opposition to the small power generation load (the first set load) of the generator 22 although the engine revolution speed N_e is as low as the predetermined low revolution speed N_{el} . This generates a large amount of combustion heat, and facilitates the warm-up of the engine 24. More specifically, loading the generator 22 makes it possible to warm up the engine 24 more quickly within a shorter period than in the case where the unloaded generator 22 is operated. In this case, there is no necessity of raising the engine revolution speed N_e .

[0025] If the engine revolution speed N_e is maintained at the predetermined low revolution speed N_{el} (e.g., 500rpm) during the warm-up of the engine 24, the engine 24 can be kept quiet with reduced noise and vibration. Moreover, it is possible to prevent each sliding part of the engine 24 from being damaged by the increase in the engine revolution speed in the case where the engine 24 is cold and is not completely smooth. This extends the life of the engine 24.

[0026] More specifically, the warm-up control device of the present invention can warm up the engine 24 while extending the life of the engine 24. In a next step S28, it is determined whether or not the engine temperature T_e is higher than a second predetermined temperature T_{we} ($T_{we} > T_w$) preset as a warm-up completion temperature ($T_e > T_{we}$). If no, the warm-up of the engine 24 is continued in a step S16. If yes, the process goes to a step S24 where it is determined that the warm-up is completed and the application of the power generation load is finished.

[0027] If no, i.e., it is determined in the step S14 that the engine temperature T_e is not greater than the first predetermined temperature and the engine 24 is quite cold, the process goes to a step S20. In the step S20, a medium power generation load (the second set load) is applied. More specifically, a load equivalent to a medium power generation (the second set load) is applied to the engine 24 to thereby warm up the engine 24.

[0028] In more detail, as is the case with the application of the small power generation load, the medium power generation load (the second set load) higher than the small power generation load (the first set load) is applied to the generator 22 to cause the generator 22 to generate medium power. On the other hand, the engine controller 48 issues an engine output command to

the engine 24 in order to maintain the engine revolution speed N_e at a predetermined low revolution speed N_{el} (e.g., 500rpm) against the medium power generation load (the second set load). More specifically, fuel injection information is supplied to a fuel injection valve (not shown) of the engine 24 in order to make it possible to maintain the engine revolution speed N_e at the predetermined low revolution speed N_{el} against the medium power generation load (the second set load) of the generator 22.

[0029] Fig. 3 shows a relationship between a generator revolution speed $N_g (=N_e)$ and a generation torque T_g of the generator 22 or a load. If the load (the second set load) equivalent to the medium power generation is applied to the engine 24, the medium power generation load (the second set load T_{g2} : white circle) higher than the small power generation load (the first set load T_{g1} : black circle) is applied to the generator 22. The engine 24 is controlled so as to maintain the generator revolution speed $N_g (=N_e)$ at the predetermined low revolution speed $N_{gl} (=N_{el}: 500rpm)$.

[0030] Therefore, the engine 24 injects a larger quantity of fuel from the fuel injection valve than fuel required for operating the unloaded generator 22 to thereby achieve an engine output in opposition to the medium power generation load (the second set load) of the generator 22 although the engine revolution speed N_e is as low as the predetermined low revolution speed N_{el} . This generates a large amount of combustion heat, and facilitates the warm-up of the engine 24.

[0031] More specifically, the medium power generation (the second set load) higher than the small power generation (the first set load) is applied to the generator 22, and the engine 24 is controlled so as to maintain the engine revolution speed N_e at the predetermined low revolution speed N_{el} . This makes it possible to warm up the engine 24 more quickly within a shorter period than in the case where the generator 22 with the small power generation load (the first set load) is operated. At the same time, it is possible to keep the quietness of the engine 24 and extend the life of the engine 24.

[0032] As is the case with the step S18, it is determined in a step S22 whether the engine temperature T_e is higher than the second predetermined temperature T_{we} ($T_e > T_{we}$) or not. If no, the warm-up of the engine 24 is continued in the step S20. If no, the process goes to the step S24 where it is determined that the warm-up is completed. Accordingly, the application of the power generation load is finished.

[0033] If the warm-up of the engine 24 is completed, the engine revolution speed N_e is raised from the predetermined revolution speed N_{el} as is normal to cause the generator 22 to start generating the power.

[0034] According to the above embodiment, the load of the generator 22 can be divided into the following two stages: the small power generation load equivalent to the small power generation (the first set load) and the medium power generation load equivalent to the medium

um power generation (the second set load). The present invention, however, should not be restricted to this. For example, the load of the generator 22 may be changed in a plurality of stages according to the engine temperature T_e , and accordingly, the engine 24 may be controlled so as to maintain the engine revolution speed N_e at the predetermined low revolution speed N_{e1} .

[0035] According to the above embodiment, whether the engine is cold or not is determined according to the engine temperature. The present invention, however, should not be restricted to this. For example, whether the engine is cold or not may be determined according to a period from the stop to the start of the engine.

[0036] It should be understood, however, that there is no intention to limit the invention to the specific forms disclosed, but on the contrary, the invention is to cover all modifications, alternate constructions and equivalents falling within the spirit and scope of the invention as expressed in the appended claims.

Claims

1. A hybrid electric vehicle comprising:

a generator (22) being rotated by a driving force of an engine (24) to generate power and supply the power to a battery (12) or a motor (10);
a temperature sensing device (48) for sensing a temperature of said engine; and
a warm-up control device (40) for controlling a load of said generator and an output of said engine so as to maintain a revolution speed of said engine at a predetermined revolution speed, if the temperature of said engine sensed by said temperature sensing device is not greater than a set temperature.

2. A hybrid electric vehicle according to claim 1, wherein:

said warm-up control device changes the load of said generator according to the temperature sensed by said temperature sensing device.

3. A hybrid electric vehicle according to claim 1, wherein:

said warm-up control device increases the load of said generator as the temperature sensed by said temperature sensing device is lowered.

4. A hybrid electric vehicle according to claim 1, wherein:

said warm-up control device has a first set load and a second set load higher than said first set load in order to change the load of said generator, and determines the load of said generator according to the temperature sensed by said temperature sensing device.

5. A hybrid electric vehicle according to claim 4, wherein:

If the temperature sensed by said temperature sensing device is higher than a first predetermined temperature lower than said set temperature, said warm-up control device changes the load of said generator to said first set load; and if the temperature sensed by said temperature sensing device is lower than said first predetermined temperature, said warm-up control device changes the load of said generator to said second set load.

6. A hybrid electric vehicle according to claim 1, wherein:

said warm-up control device finishes controlling the load of said generator and the output of said engine when the temperature sensed by said temperature sensing device exceeds a second preset temperature higher than said set temperature.

7. A hybrid electric vehicle comprising:

a generator (22) being rotated by a driving force of an engine (24) to generate power and supply the power to a battery (12) or a motor (10); and a warm-up control device (40) for increasing a load of said generator and controlling an output of said engine so as to maintain a revolution speed of said engine at a predetermined revolution speed after starting said engine in a cold state.

Fig. 1




Fig. 2





Fig. 3





(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
17.04.2002 Bulletin 2002/16

(51) Int Cl.7: **B60K 41/00, B60L 11/12**

(43) Date of publication A2:
29.08.2001 Bulletin 2001/35

(21) Application number: 01103474.1

(22) Date of filing: 14.02.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
 Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 16.02.2000 JP 2000038602

(71) Applicant: **Mitsubishi Jidosha Kogyo Kabushiki Kaisha**
Tokyo 108-8410 (JP)

(72) Inventors:

- **Takashi, Yanase,**
c/o Mitsubishi Jidosha Kogyo K.K.
Tokyo (JP)
- **Makoto, Ogata,**
c/o Mitsubishi Jidosha Kogyo K.K.
Tokyo (JP)


(74) Representative: Kern, Ralf M., Dipl.-Ing.
Hansastraße 16/II.
80686 München (DE)

(54) Warm-up control device of hybrid electric vehicle

(57) The invention provides a warm-up control device of a hybrid electric vehicle, which warms up an engine for generator while extending the life of the engine and improves the quietness. If an engine temperature is not greater than a set temperature after the start of

the engine for generator, the warm-up control device controls a load of the generator and controls an engine output in accordance with the load of the generator so as to maintain an engine revolution speed at a predetermined low revolution speed.

Fig. 1





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 10 3474

DOCUMENTS CONSIDERED TO BE RELEVANT			Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Category	Citation of document with indication, where appropriate, of relevant passages			
X	EP 0 698 520 A (HONDA MOTOR CO LTD) 28 February 1996 (1996-02-28) * abstract; figures * * column 1, line 27 - line 31 * * column 3, line 29 - line 55 * * column 11, line 26 * * column 14, line 54 - column 15, line 9 *	1,2,7	B60K41/00 B60L11/12	
A	DE 195 05 431 A (BAYERISCHE MOTOREN WERKE AG) 22 August 1996 (1996-08-22) * abstract; figures *	1		
A	DE 41 33 059 A (MANNESSMANN AG) 8 April 1993 (1993-04-08) * abstract; figures *	1		
The present search report has been drawn up for all claims				TECHNICAL FIELDS SEARCHED (Int.Cl.7)
				B60K B60L
Place of search		Date of completion of the search	Examiner	
THE HAGUE		21 February 2002	Wagner, H	
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>				

EPO FORM 1503 (03.02.92) (P/4001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 10 3474

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-02-2002

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 0698520	A	28-02-1996	JP	2738819 B2	08-04-1998
			JP	8061106 A	05-03-1996
			DE	69519456 D1	28-12-2000
			DE	69519456 T2	12-04-2001
			EP	0698520 A1	28-02-1996
			US	5608308 A	04-03-1997
DE 19505431	A	22-08-1996	DE	19505431 A1	22-08-1996
			US	5788004 A	04-08-1998
DE 4133059	A	08-04-1993	DE	4133059 A1	08-04-1993
			BR	9206412 A	28-03-1995
			BR	9206589 A	21-11-1995
			CN	1074868 A	04-08-1993
			CN	1074870 A	04-08-1993
			WO	9307019 A1	15-04-1993
			WO	9307022 A1	15-04-1993
			DE	59201988 D1	24-05-1995
			DE	59207734 D1	30-01-1997
			EP	0606297 A1	20-07-1994
			EP	0606316 A1	20-07-1994
			ES	2071514 T3	16-06-1995
			JP	2805546 B2	30-09-1998
			JP	6511134 T	08-12-1994
			JP	6511616 T	22-12-1994
			MX	9205690 A1	01-07-1993
			MX	9205691 A1	01-07-1993
			US	5461289 A	24-10-1995

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

